BEHR® Solid Color House & Fence Wood Stain

- Oil-Latex Formula
- Self-Priming
- Resists Moisture, Cracking & Blistering
- Mildew Resistant Finish

Must Prep Before Staining

2 Thin Coats Recommended

Spread Rate:
1st Coat 200-400 Sq. Ft.
2nd Coat 250-500 Sq. Ft.

Soap & Water Clean-Up

CAUTION: Stained surfaces may become slippery when wet.

WHERE TO USE

Recommended for smooth or rough sawn exterior vertical wood surfaces such as: Plywood, Fences, Patio Covers, Shingles, Shakes, Siding, Laminates, Barns and Masonry & Stucco Surfaces. *Do not use on horizontal surfaces subject to foot traffic.*

PREPARATION †

(The following steps and products are required.) Use a product such as BEHR PREMIUM® NO. 64 Wood Stain & Finish Stripper on failing areas to remove latex, oil-based and 100% acrylic coatings. BEHR PREMIUM NO. 63 All-In-One Wood Cleaner MUST be used following NO. 64 to clean, brighten & neutralize wood. When NO. 64 is not needed, use a product such as NO. 63 to clean and brighten the wood surface and to remove light to medium exterior stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as NO. 63 to remove mill glaze and open the pores of the wood. Lightly sand to remove remaining wood fibers/fuzz.

APPLICATION

Must apply between 40-90˚ F (4.5-32˚ C). Do not use if rain is expected within 24 hours. The wood surface must be completely dry before application. No primer needed on most woods. However, Redwood, Cedar, Cypress and other "bleeding" woods contain water soluble extractives which may cause discoloration of white and pastel colors; therefore prime the above type woods with one coat of a product such as BEHR PREMIUM PLUS® NO. 436 Exterior Multi-Purpose Primer & Sealer. See label for additional instructions. Intermix multiple containers to ensure color uniformity. Apply with a nylon/polyester brush. On rough-sawn or textured wood apply with a 3/4" (19 mm) long nap roller or high quality airless sprayer. For airless spraying use a .015 - .019" tip. Pump Sprayer not recommended. Always back-brush or back-roll during all application methods. Keep a wet edge to reduce lapping and help control color uniformity. Over application of stain will lead to surface failure including peeling and cracking. **Avoid applying stain too heavily. Two thin coats recommended.**

WARRANTY

- Visit www.Behr.com for complete warranty information.

DRY TIME

6-8 hours before recoat. Allow 72 hours for full cure.

DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2013 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 3/13